

## DECLARATION OF PERFORMANCE

No.: 007-1-CPR-2013

### IZEON®

1	Unique identification code of the <b>product-type</b>	IZEON®
2	<b>Type, batch</b> or serial <b>number</b> or any other element allowing identification of the construction product as required pursuant to Article 11(4)	IZEON® batch numbers on panel label
3	<b>Intended use</b> or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Compact laminate panels for external wall and ceiling finishes Type EDS according to EN438 part 6
4	<b>Name</b> , registered trade name or registered trade mark and <b>contact address</b> of the <b>manufacturer</b> as required pursuant to Article 11(5)	TRESPA International B.V. Wetering 20 NL – 6002 SM Weert
5	Where applicable, <b>name</b> and <b>contact address</b> of the <b>authorized representative</b> whose mandate covers the tasks specified in Article 12(2)	-
6	<b>System</b> or systems of <b>AVCP</b> (=assessment and verification of constancy of performance) of the construction product as set out in Annex V of CPR	System 3
7	Name and identification number of the notified body in case of DoP concerning a construction product covered by a harmonized standard	Notified test laboratory 1173 determined product-type on basis of type testing.

## DECLARATION OF PERFORMANCE

No.: 007-1-CPR-2013

8 Declared performance		
Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	D-s2,d0	EN 438 - 7
Fire Resistance	NPD	
Water vapour permeability	NPD	
Resistance to fixings	6 mm ≥ 2.000 N 8 mm ≥ 3.000 N ≥ 10 mm ≥ 4.000 N	
Direct airborne sound insulation	NPD	
Flexural tensile strength	≥ 120 MPa	
Flexural modulus of elasticity	≥ 9000 MPa	
Thermal resistance / conductivity	NPD	
Release of formaldehyde	E1	
Sound absorption	NPD	
Thermal shock resistance	pass	
Durability: Resistance to wet conditions	pass	
Durability: Density	≥ 1,35 g/m <sup>3</sup>	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Weert, 01.07.2013

.....  
Paul Booms (COO)

.....  
Christine Klomp (Product compliance officer)