



BRUYNZEEL MULTIPANEL

MULTIPAIN'T

OUTDOOR PANELS ► BUILDING AND MARINE



DESCRIPTION

Up graded exotic plywood for outdoor applications with phenolic film on both faces

USINGS

This product is especially suitable for outdoor panels, cladding, walls, shutters, requiring high quality painted finishes

ADVANTAGES

- ✓ Naturally sustainable wood
- ✓ Selected veneers and excellent mechanical resistance
- ✓ 15 years guarantee
- ✓ Pre-painted faces, no work preparation, high gloss finish

COMPOSITION

Face 1 and Face 2 : Phenolic film

Inner layers in selected peeled exotic veneers

(natural whole piece free of defect or edge glued jointed veneers, no split, no overlap, no defect telegraphing through the face veneers)

WOOD SPECY

Okoume (500 kg/m3 +/-10%)

GLUING

EN 314-2 : Class 3 (EN 636-3) Exterior using

EN 717-2 : E1 very low formaldehyde emission

SIZES

Regular sizes in mm : 2500x1220

THICKNESSES

mm	10	12	15	18
plies	7	7	9	11

Surface finishing sanded 2 faces

For any other thickness and size, please contact us

OPTIONS

Cut at size, CNC milling, painting (wide range of colour)

Guarantee

Exterior Carpentry

15 years

SAS ALLIN

RUE DE LA COUARDE - F-79270 LE VANNEAU

Tel : +33 5 49 35 00 02 – Fax : +33 5 49 35 02 64

E-mail : allin-sa@allin.fr – Site web : www.allin.fr